Savin MLP75n

SPECIFICATIONS

Configuration

Laser-beam scanning, electro-photographic printing Technology

with dual-component toner development PCL 5e: 300 x 300, 600 x 600 dpi PCL 6: 600 x 600, 1200 x 1200 dpi Resolution

RPCS: 300 x 300, 600 x 600, 1200 x 1200 dpi

PS 3: 600 x 600, 1200 x 1200 dpi

Printing Speed 75 ppm

Duplex Speed Approximately 100% productivity of simplex speed

5.5 seconds or less First Print Speed

Dimensions (WxDxH) 27.17" x 29.92" x 57.72" (690 x 760 x 1466 mm)

without finisher 407.86 lbs (185 kg) Weight Warm-up Time Less than 300 seconds

120V/60Hz/20A (Requires Dedicated 20A Outlet) Power Source

Power Consumption Less than 1.85 KW 50 W **Energy Saver Mode**

Paper Capacities Up to 8,300 Sheets

1st Tray: 1,550 x 2 = 3,100 sheets 2nd and 3rd Tray: 550 sheets each

Bypass Tray: 100 sheets

Optional Large Capacity Tray (LCT): 4,000 sheets

Output Capacity

500 sheets 5.5" x 8.5" to 11" x 17" (12" x 18" through Paper Sizes Bypass Tray)

Standard: 14 - 34 lb. (52 - 128 g/m²) Paper Weight

Bypass: 14 - 58 lb./80 lb. Cover (52 - 216 g/m²)

LCT: 14 - 34 lb. (52 - 128 g/m²) Plain paper, recycled paper*, thick paper, Acceptable Paper Types

laser printer qualified transparencies* and tabs** *Only available with optional LCT and Bypass

**Only available with the Tab Sheet Option Safety Regulations UL ÚL60950, FCC Part 15 Class B

CONTROLLER SPECIFICATIONS

RPCS, PCL 5e/PCL 6, Adobe PostScript 3, PDF **Printer Languages**

Adobe PostScript 3: 136 Type 1 fonts; **Fonts**

PCL: 45 Intellifonts; 10 TrueType fonts; 1 bitmap font; Memory 384 MB/40 GB HDD

Standard Interfaces 10/100 Base TX, Parallel IEEE 1284

Wireless LAN Interface IEEE 802.11b, USB 2.0 Optional Interfaces

Network Protocols Drivers

TCP/IP, IPX/SPX, Apple Talk, SMB PCL 5/6 and RPCS: Windows 95/98SE/NT4.0/2000/ Me/XP/Server 2003; PS3: Windows 95/98SE/NT4.0/ 2000/Me/XP/Server 2003; Macintosh 8.6-9.2x (OS X Classic), Mac OS X Native (v. 10.1 or later) UNIX: Solaris, HP-UX, Red Hat Linux, SCO, IBM AIX **Print Utilities**

SmartDeviceMonitor for Administrator and Client Web SmartDeviceMonitor; Web Image Monitor; DeskTopBinder Lite; Printer Utility for Mac;

Agfa Font Manager 2000

CONTROLLER OPTIONS

USB 2.0 Interface Type B* IEEE 802.11b Wireless LAN Type H*

*Only one additional interface can be installed.

SECURITY FEATURES

Network Data Protection Unit Type B

Enables data encryption to prevent information theft.

Other Security Features

Authentication Locked Print Encryption















OPTIONAL PAPER HANDLING ACCESSORIES

Large Capacity Tray (LCT) (RT43)

8.5" x 11" LEF 14 - 34 lb. Original Size Original Paper Weight

4,000 sheets (20 lb. bond) Paper Capacity

8.5" x 14" Option for LCT Type 1075

Enables the feeding of legal-size (8.5 x 14) paper through LCT

Original Size

8.5" x 14", 8.5" x 11" SEF

Paper Capacity

2,500 sheets (20 lb. Bond)

11" x 17" Paper Size Tray Type 1075 Enables the feeding of 11" x 17" a Enables the feeding of 11" x 17" and 8.5" x 14" paper from Tray 1, which is normally tandem 8.5" x 11" only.

Paper Size

11" x 17" SEF, 8.5" x 14" SEF, 8.5" x 11"

Paper Capacity

1,000 sheets

Paper Capacity

Tab Sheet Unit (Tab Sheet Holder Type 1075)

Necessary to feed tab sheets from Tray 2 or Tray 3 (Both trays cannot

feed tabs)

OPTIONAL FINISHERS

3000 Sheet Finisher w/100 Sheet Stapler (SR841)

Proof Tray: Stack Capacity 250 sheets (8.5" x 11" or smaller) Shift Tray: Stack Capacity 3,000 sheets (8.5" x 11")

Paper Size* 5.5" x 8.5" - 11" x 17"

Paper Weight* 14 lb. Bond - 80 lb. Cover (216 g/m²)

*For both Proof Tray and Shift Tray

Staple Capacity per Set

100 sheets (L8.5" x 11"); 50 sheets (11" x 17", 8.5" x 14", 8.5" x 11" SEF)

Top, Bottom, 2 staples, Top Slant Staple Positions

Hole Punching Option (Punch Unit Type 1075) **Hole Positions** 2 or 3 holes switchable

Output Jogger Unit Type 1075

Secures each finished set in an orderly fashion. Available with SR841 only

3000 Sheet Finisher with Saddle Stitch (SR861 Finisher)

Proof Tray: Stack Capacity 250 sheets (8.5" x 11" or smaller)

Upper Shift Tray:

Stack Capacity 500 sheets (8.5" x 11") 5.5" x 8.5" - 11" x 17" Paper Size* Paper Weight*

14 lb. Bond - 90 lb. Index

*For both Proof Tray and Upper Shift Tray

Lower Shift Tray:

2,500 sheets (8.5" x 11" LEF) 5.5" x 8.5" - 11" x 17" Stack Capacity

Paper Size

5.5 x 6.5 - 11 x 17 14 lb. Bond - 80 lb. Cover (216 g/m²) 50 sheets (8.5" x 11" or smaller) 30 sheets (8.5" x 14" or larger) 15 sheets (8.5" x 11 - 11" x 17") Top, Bottom, 2 staples, Top Slant Paper Weight Staple Capacity Saddle Stitch

Staple Position Saddle Stitch Position Center 2 positions

Center Folding w/o stitch 1 sheet

Hole Punching Option (Punch Unit Type 1045) Hole Positions 2 or 3 holes (switchable)

Cover Interposer Tray (Type 1075) Available with both finishers.

200 sheets (20 lb. Bond) Paper Capacity

Copy Tray (Copy Tray Type 1075)

Copy Tray is an option to receive output when configured without a finisher.

Paper Capacity 500 sheets

CONSUMABLES

Black Toner Cartridge Yield: 43,000 pages/bottle pages @ 5%

Savin Five Dedrick Place, West Caldwell, NI 07006









